

Solis

**THE TOUGHEST
PERFORMER
FOR YOUR FIELD**

26



**AERODYNAMIC
BONNET**

**POWER PACKED
MITSUBISHI ENGINE**

**TWIN PROJECTOR
HEADLAMPS**

**AGRI, IND. & TURF
TYRE OPTION**

**REINFORCED SAFETY
FEATURES**



**COST
EFFICIENT**
MECHANICAL TRACTORS

MADE OF
**REAL
STEEL**

STRATEGIC
COLLABORATION
WITH
YANMAR

**THE TOUGHEST
PERFORMER
« FOR YOUR FIELD »**

26

Solis



FEATURES	26
ENGINE	
Engine Type	Mitsubishi 3-Cylinder Diesel Motor
HP Category	26
No. of Cylinders	3
Aspiration	Naturally
Cubic Capacity (cc)	1319
Rated RPM (+/-25mm)	2500
Air Cleaner	Dry with clogging sensor
Cold Start	Standard
Max Torque (Nm)	76.3
Exhaust	Silencer in the engine compartment, downward discharge
TRANSMISSION	
Drive	4 WD
Clutch	Single Clutch
Gearbox	6 Forward + 2 Reverse
Front Axle	4WD
Transmission	Sliding Mesh
SPEED (FORWARD)	
Maximum Speed (Km/Hr)	16.2@2815 fly up
Minimum Speed (Km/Hr)	1.64@2500 rated
BRAKES	
Brakes	Oil Bath Brake
Type of Actuation	Mechanical
Parking Brake	Independent
Differential Lock	
Differential Lock	Yes, Foot Operated
PTO	
PTO (rpm)	540, 1000
PTO (actuation)	Mechanical
STEERING	
Steering	Power steering
ELECTRICAL	
Battery	12V, 65 Ah
Alternator	12V, 42 A
Seven Pin Trailer Socket	Standard
HYDRAULICS	
3 Point Linkage	Cat 1-N
Stay Bars	Anchor Chain
Additional hydraulic circuit	1 DW
Hydraulic Lifting Capacity	600 Kg
Lift Rods	Standard
Litre per Minute(LPM)	13.5

FEATURES	26		
SAFETY SWITCH			
PTO Safety	Standard		
Neutral Safety Switch	Standard		
Clutch Safety Switch	Standard		
CAPACITY (LTRS)(+/-5%)			
Fuel Tank (Lit)	28		
TURNING RADIUS			
Without brakes (m) as per standard tyres	3.18 (RHS), 3.10 (LHS)		
TYRE			
Front	6.00-12		
Rear	8.30-20		
DIMENSION & WEIGHT(+/-5%)			
Weight (Kg)	1070, 1265 with Cabin		
Wheel Base (mm)	1560		
Total Length (mm)	2760		
Total Width (mm)	1075 (max) - 1055 (min)		
Height (mm) Up to ROPS	1955		
Min Ground Clearance (mm)	240		
Front Track (mm)	885		
Rear Track (mm)	835		
OTHERS			
Fuel Indicator Gauge	Standard		
Front Tow Hook	Standard		
Front & Rear Weights with std. Ballast	Front weights - 2 x 15 Kg		
Trailer Hitch	Drawbar / Optional Towbar		
ROPS	Yes		
OPTIONAL FEATURES			
Cabin Option	Optional only heater		
Tyres			
Radial Agri: Front Rear	Turf: Front Rear	Ind: Front Rear	GALAXY PRO
6.5/80-12 280/70 R18	23x8.50-12 33x15.5-16.5	23x8.50-12 33x15.5-16.5	FRONT 220/55R12 REAR 280/70R16
Front loader	YES optional		

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

DEALER STAMP



INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221

Fax: +91- 01882-522222 | Email: info@solis.com | URL: www.solistractors.com/www.solisworld.com